Square Pedestal Mount Outdoor Drinking Fountain

STANDARD FEATURES

- Resistant to sunlight, heat, moisture and wear
- 18 gage, 304 stainless steel bowl
- 12 gage, heavy duty stainless steel, corrosion and scratch resistant finish
- Polished stainless steel, anti-rotation non-squirt bubbler
- 100 mesh inlet strainer
- Access door, heavy duty stainless steel, vandal resistant

SUGGESTED SPECIFICATIONS

Square Pedestal Mount Outdoor Drinking Fountain- is a pedestal mounted, vandal resistant square drinking fountain made from an 18 gage, 304 stainless steel bowl mounted into a green powder coated 12 gage, heavy duty stainless steel pedestal. Unit shall be activated by a front mounted self-closing button, by using less than 5 pounds of force, which activates an internally mounted valve with an adjustable stream regulator controlling the water flow. Bubbler shall be polished stainless steel with a non-squirt feature and operate on water pressure range of 20-105 psig. Unit shall adhere to NSF/ANSI 61, Section 9, Public Law 111-380 (NO-LEAD), and CHSC 116875.

Options Notes:

¹ See separate option sheet.

² This option is not available freeze-resistant.



MODEL:

(Must Specify)

Satin stainless finish Green powder-coated (Shown) Red powder-coated

Blue powder-coated

Custom color finishes available upon request

OPTIONS

(additional costs may be incurred)

☐ -CH30	Child height, 30" bubbler height
🔲 -FRU1	Freeze resistant, 1 valve ¹
🔲 -FRU2	Freeze resistant, 2 valves ¹
🔲 -FRU3	Freeze resistant, 3 valves ¹
🔲 -FS	Foot spray
🔲 -HB1	Hose bibb, compression, with hose threaded outlet/VB 1 2
☐ -HB2	Hose bibb, loose key, with hose threaded outlet/VB ^{1 2}
☐ -HB3	Hose bibb, loose key, vandal resistant, with hose threaded outlet/VB ^{1 2}
🔲 -IGM	In-ground 14" mounting
🔲 -JF1	Jug filler, spigot, self-closing valve with plain end ^{1 2}
☐ -JF2	Jug filler, pushbutton, self-closing valve with plain end ¹
🔲 -NP1	Non-pollutable, freeze resistant, 1 valve
-NP2	Non-pollutable, freeze resistant, 2 valves
-NP3	Non-pollutable, freeze resistant, 3 valves
🔲 -PF	Pet fountain receptor 1



Member of U.S. Green Building Council



Recyclable Product













IMPORTANT: INSTALLATION AND SITE PREP FOR FREEZE RESISTANT OPTIONS "-FRU, -NP" WILL DIFFER FROM STANDARD. REFER TO DESIGNATED FREEZE RESISTANT INSTALLATION DETAILS.

ACCESS PANEL 13" [330] 13" [330] 18" - \bigcirc [36] WASTE OUTLET *418" [1052] Valve specifications: Minimum/Maximum Pressure 30 to 100 psi. PROVIDED ANCHORS

PEDESTAL MOUNTED **DRINKING FOUNTAIN**

GENERAL NOTES:

- 1. ALL DIMENSIONS ARE IN INCHES [MM].

 *2. STANDARD ADULT HEIGHT MODEL SHOWN. OPTIONAL -CH30 CHILD HEIGHT MODEL AVAILABLE.
- 3. STOP VALVE NOT PROVIDED.