

Square Pedestal Push Button Pet Shower

STANDARD FEATURES

- Pushbuttons requiring less than 5 pounds for activation
- Adjustable timing, from 5 to 60 seconds
- Chrome plated brass shower heads with 2.5 gpm flow controls and adjustable spray pattern
- Vandal resistant fasteners
- Shut off valve for easy servicing
- Heavy duty, 14 gage, 304 stainless steel construction with corrosion and scratch resistant satin finish

SUGGESTED SPECIFICATIONS

Unit is to be pre-piped and hydrostatically tested.

Valves shall have internally mounted metering valve, pushbutton operated and requiring less than 5 pounds of force to activate. Timing shall be adjusted from 5 to 60 seconds.

Shower head shall be chrome plated brass with 2.5 gpm flow restrictor and include an adjustable spray pattern from a coarse stream to a fine mist.

Unit shall be constructed of heavy duty 14 gage type 304 stainless steel polished to a satin finish with vandal resistant fasteners and shall include a 1/4" thick stainless steel bottom plate, providing secure mounting for shower.



MODEL:

(Must Specify)

Satin Stainless Finish (Standard)
Green Powder-Coated
Red Powder-Coated
Blue Powder-Coated
Custom color finishes available upon request

OPTIONS

(additional costs may be incurred)

- FRU1 Underground freeze-resistant valve for one pushbutton ¹
- IAP In-ground anchor plate (replaces standard anchor plate)¹
- LOGO Customer specified logo¹

Option Notes:

¹ See separate option sheet.



Member of
U.S. Green
Building
Council



Recyclable
Product

Complies with the
following standards:



ANSI / NSF 61.9



GREEN
UPC
Water Efficiency



Public Law
111-380
(No Lead)

